

SC4H160D2

Used for 100kVA generator



◎ POWER RATING

Engine Speed rpm	Type of Operation	Engine Power	
		kW	Ps
1500	Prime Power	105	143
	Standby Power	116	160

- The engine performance is as per GB/T2820.

- Ratings are based on GB/T1147.1.

---Prime power is available for an unlimited number of hours per year in a variable load application. The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

---Standby power is available in the event of a utility power outage or under test conditions for up to 200 hours of operation per year.

The permissible average power output over 24 hours of operation shall not exceed 80% of the standby power rating.

◎ SPECIFICATIONS

◎ FUEL CONSUMPTION

○ Engine Model	SC4H160D2	○ Power	lit/hr
○ Engine Type	In-line,4 strokes, water-cooled	25%	6.6
	4 valves, Turbo charged	50%	12.8
	air-to-air intercooled	75%	16.7
○ Combustion type	Direct injection	100%	25.0
○ Cylinder Type	Dry liner	110%	27.7
○ Number of cylinders	4		
○ Bore × stroke	105(4.14) × 124(4.89) mm(in.)		
○ Displacement	4.3(262.4) lit.(in3)		
○ Compression ratio	16 : 1		

◎ FUEL SYSTEM

○ Firing order	1-3-4-2	○ Injection pump	Longkou in-line “P” type
○ Injection timing	11°BTDC	○ Governor	Electric type
○ Dry weight	Approx. 450kg (992.1 lb)	○ Feed pump	Mechanical type
○ Dimension	1053×717×1158 mm	○ Injection nozzle	Multi hole type
(L×W×H)	(41.5×28.3×45.6 in.)	○ Opening pressure	250 kg/cm2 (3556 psi)
○ Rotation	Counter clockwise viewed from Flywheel	○ Fuel filter	Full flow, cartridge type

- Fly wheel housing SAE NO.3
- Fly wheel SAE NO.11.5
- Used fuel Diesel fuel oil

◎ **MECHANISM**

- Type Over head valve
- Number of valve Intake 2, exhaust 2 per cylinder
- Valve lashes at cold
Intake 0.25mm (0.0099 in.)
Exhaust 0.50mm (0.0197 in.)

◎ **VALVE TIMING**

- | | Opening | Close |
|-----------------|------------|------------|
| ○ Intake valve | 20.9° BTDC | 44.9° ABDC |
| ○ Exhaust valve | 51.7° BBDC | 11.7° ATDC |

◎ **COOLING SYSTEM**

- Cooling method Fresh water forced circulation
- Water capacity 6.8 liters (1.8 gal.)
(engine only)
- Pressure system Max. 0.5 kg/cm² (7.11 psi)
- Water pump Centrifugal type driven by belt
- Water pump Capacity 155 liters (136 gal.)/min
at 1,500 rpm (engine)
- Thermostat Wax–pellet type
Opening temp. 82°C
Full open temp. 95°C
- Cooling fan Blower type, plastic
620 mm diameter, 10 blades
- Cooling air flow 3.09 m³ /s

◎ **LUBRICATION SYSTEM**

- Lub. Method Fully forced pressure feed type
- Oil pump Gear type driven by crankshaft
- Oil filter Full flow, cartridge type
- Oil pan capacity High level 13 liters (3.4 gal.)
Low level 11 liters (2.9 gal.)
- Angularity limit Front down 25 deg.
Front up 35 deg.
Side to side 35 deg.
- Lub. Oil Refer to Operation Manual

◎ **ENGINEERING DATA**

- Water flow 155 liters/min @1,500 rpm
- Heat rejection to coolant 15.5 kcal/sec @1,500 rpm
- Heat rejection to CAC 7.8 kcal/sec @1,500 rpm
- Air flow 7.39 m³/min @1,500 rpm
- Exhaust gas flow 16.3 m³/min @1,500 rpm
- Exhaust gas temp. 600 °C @1,500 rpm
- Max. permissible restrictions
Intake system 3 kPa initial
6 kPa final
Exhaust system 6 kPa max.
- Max. permissible altitude 2,000 m
- Fan power 5 kW

◎ ELECTRICAL SYSTEM

- Charging generator 24V×55A
- Voltage regulator Built-in type IC regulator
- Starting motor 24V×4.5kW
- Battery Voltage 24V
- Battery Capacity 120 AH

◆ CONVERSION TABLE

- in. = mm × 0.0394
- lb/ft = N.m × 0.737
- PS = kW × 1.3596
- U.S. gal = lit. × 0.264
- psi = kg/cm² × 14.2233
- kW = 0.2388 kcal/s
- in³ = lit. × 61.02
- lb/PS.h = g/kW.h × 0.00162
- hp = PS × 0.98635
- cfm = m³/min × 35.336
- lb = kg × 2.20462

