

SC9D340D2

Used for 250kVA generator



SDEC

◎ POWER RATING

Engine Speed rpm	Type of Operation	Engine Power	
		kW	Ps
1500	Prime Power	228	310
	Standby Power	255	340

- The engine performance is as per GB/T2820.

- Ratings are based on GB/T1147.1.

---Prime power is available for an unlimited number of hours per year in a variable load application. The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

---Standby power is available in the event of a utility power outage or under test conditions for up to 200 hours of operation per year.

The permissible average power output over 24 hours of operation shall not exceed 80% of the standby power rating.

◎ SPECIFICATIONS

○ Engine Model	SC9D340D2
○ Engine Type	In-line,4 strokes, water-cooled 4 valves, Turbo charged air-to-air intercooled
○ Combustion type	Direct injection
○ Cylinder Type	Wet liner
○ Number of cylinders	6
○ Bore × stroke	114(4.49) × 144(5.67) mm(in.)
○ Displacement	8.82(538.2) lit.(in3)
○ Compression ratio	16.5 : 1
○ Firing order	1-5-3-6-2-4
○ Injection timing	8.5°BTDC
○ Dry weight	Approx.840 kg (1852 lb)
○ Dimension (L×W×H)	1578×778×1290 mm (62.2×30.7×50.8 in.)
○ Rotation	Counter clockwise viewed from Flywheel

◎ FUEL CONSUMPTION

○ Power	lit/hr
25%	14.7
50%	27.3
75%	40.8
100%	54.1
110%	59.6

◎ FUEL SYSTEM

○ Injection pump	Longkou in-line “P” type
○ Governor	Electric type
○ Feed pump	Mechanical type
○ Injection nozzle	Multi hole type
○ Opening pressure	250 kg/cm2 (3556 psi)
○ Fuel filter	Full flow, cartridge type

○ Fly wheel housing	SAE NO.2	○ Used fuel	Diesel fuel oil
○ Fly wheel	SAE NO.11.5		

⊙ **MECHANISM**

○ Type	Over head valve
○ Number of valve	Intake 2, exhaust 2 per cylinder
○ Valve lashes at cold	Intake 0.30mm (0.0118 in.) Exhaust 0.55mm (0.0217 in.)

⊙ **VALVE TIMING**

	Opening	Close
○ Intake valve	29.5 deg. BTDC	42. 5deg. ABDC
○ Exhaust valve	69.5 deg. BBDC	34.5 deg. ATDC

⊙ **COOLING SYSTEM**

○ Cooling method	Fresh water forced circulation
○ Water capacity (engine only)	12 liters (3.17 gal.)
○ Pressure system	Max. 0.5 kg/cm ² (7.11 psi)
○ Water pump	Centrifugal type driven by belt
○ Water pump Capacity	200 liters (52.8 gal.)/min at 1,500 rpm (engine)
○ Thermostat	Wax–pellet type Opening temp. 82°C Full open temp. 93°C
○ Cooling fan	Blower type, plastic 762 mm diameter, 10 blades
○ Cooling air flow	6.97 m ³ /s

⊙ **LUBRICATION SYSTEM**

○ Lub. Method	Fully forced pressure feed type
○ Oil pump	Gear type driven by crankshaft
○ Oil filter	Full flow, cartridge type
○ Oil pan capacity	High level 25 liters (6.6 gal.) Low level 22 liters (5.8 gal.)
○ Angularity limit	Front down 25 deg. Front up 35 deg. Side to side 35 deg.
○ Lub. Oil	Refer to Operation Manual

⊙ **ENGINEERING DATA**

○ Water flow	200 liters/min @1,500 rpm
○ Heat rejection to coolant	20.35 kcal/sec @1,500 rpm
○ Heat rejection to CAC	10.2 kcal/sec @1,500 rpm
○ Air flow	18.6 m ³ /min @1,500 rpm
○ Exhaust gas flow	41 m ³ /min @1,500 rpm
○ Exhaust gas temp.	600 °C @1,500 rpm
○ Max. permissible restrictions	
Intake system	3 kPa initial 6 kPa final
Exhaust system	6 kPa max.
○ Max. permissible altitude	2,000 m
○ Fan power	8 kW

◎ ELECTRICAL SYSTEM

- Charging generator 28V×55A
- Voltage regulator Built-in type IC regulator
- Starting motor 24V×7.5kW
- Battery Voltage 24V
- Battery Capacity 180 AH

◆ CONVERSION TABLE

- in. = mm × 0.0394
- lb/ft = N.m × 0.737
- PS = kW × 1.3596
- U.S. gal = lit. × 0.264
- psi = kg/cm² × 14.2233
- kW = 0.2388 kcal/s
- in³ = lit. × 61.02
- lb/PS.h = g/kW.h × 0.00162
- hp = PS × 0.98635
- cfm = m³/min × 35.336
- lb = kg × 2.20462

