

DIESEL GENERATOR SET

Model: SSDS-338T

Rate Power: 308kVA/ 50Hz/ 3 phases

Applications:

Home, Buildings, Hospitals, Train station, Bank, Telecom, Mining, Military, Outdoor projects, etc.

Features and Benefits

- Tightly structure, excellent design and craft •
- Excellent cooling system, reliable performance • under the harshest conditions (ambient temperature up to 40°C and altitudes up to 1000m)
- Self-diagnostic capability simplifies troubleshooting
- LCD display shows system status setup • information

Color choices:

- Automatic voltage regulator protects your • sensitive electronics from harmonic distortion and unstable power quality
- Soundproof type: Very quite running: 75±3dB(A) . at 23ft(7m) at normal load.
- Enclosed muffler for added guietness •
- Service and; maintenance accessible through easy-latch side service door

Generator Data

Prime Power (kVA)	308
Standby Power (kVA)	338
Rated Frequency (Hz)	50
Running Noise db(A)/7m (Silent type)	75±3
VItage (V)	220/380
Curent (A)	446
No.Phase	3
Silent Type-Dimension (LxWxH) (mm)	4000*1400*2100
Silent Type-Weight (kg)	3980
Fuel Tank Capacity (L)	450
Fuel	Diesel
SSDS-338T	Page 1





Engine Specifications

Main features:

Brand: SDEC

- 6-cylinder, water-cooled, in-line diesel engine.
- Efficient fuel system for max power output and durability.
- Large-capacity air cleaner.
- Cost effective, fuel efficient and reliable performance.
- Functional engine with compact structure.
- Excellent after-sales service and sufficient spare parts supplying.
- Easy installation and ready access for routine maintenance

Model	SC13G420D2
Output Power (kw)	308
Cylinder No. & Config.	4, In-line
Туре	6 cycle , Diesel
Displacement (liters)	12.88
Governor	Elech type
Engine System (r/min)	1500
Air intake system	Turbo, Inter-cooled
Fuel Consumption 100% load	70.4
Oil Capacity (L)	41
Compression ratio	15.55:1

Alternator specifications

Main Features:

- Advanced automatic voltage regulator (AVR) control for trouble-free operation under the most demanding conditions.
- 2/3 pitch winding as standard, to avoid excessive neutral current.
- Single or two bearing construction with dynamically balanced rotor and sealed-for-life bearings.
- Easy access for installation and maintenance.
- IP23 as standard.
- Self-excited control system.
 Resist of corruption of oil and acid.

Brand options:	Mecc-Atle/ Leroy Somer/ Benzen
Model	4-7
Rated Power (kVA)	308
Excitation System	Brushless, self-exciting
Connection Type	3 phases, 4 wires
Pole No	4
Regulator type	AVR
Protection class	IP23
Insulation class	Н







Options:



Control Panel System



DATAKOM



COMAP

DEEP SEA

Main Features:

- Using microprocessor as a core, graphics LCD with big screen and backlight, key touch for operation
- All parameters use digital modulation, with higher reliability and stability
- Built-in speed/frequency detecting units can accurately judge the states such as crank success and over speed

Precision measure and display of:

- Generator voltage
- Generator current
- Generator frequency
- ✓ Generator active power (kW)
- Generator inactive power (kW)
- Generator apparent power (kVA)
- Generator power factor
- Generator starts count
- Generator hour count
- Cumulate electric energy (kWh)
- Generator temperature
- Generator pressure
 - Start battery voltage

- Security password-protected programming levels
- Power supply range is wide, accommodating to different starting battery voltage environment
- Built-in watch dog can never be dead halt, ensuring smooth program execution
- Modular configuration design, inserted type connection terminals, flush type installation, compact structure, easy installation

Protection:

- Emergency stop
- High water temperature
- Low oil pressure
 - Over speed
- Under speed
- Loss of speed signal
- Generator over frequency
- Generator under frequency
- Generator over voltage
- Generator under voltage
- Generator over current
- Fail to start
 - Auxiliary inputs

* Reserves the right to change the specifications and designs without notice.

