

DIESEL GENERATOR SET

Model: YDS-10T

Rate Power: 9kVA/ 50Hz/ 3 phases

Applications:

Home, Buildings, Hospitals, Train station, Bank, Telecom, Mining, Military, Outdoor projects, etc.

Features and Benefits

- Tightly structure, excellent design and craft •
- Excellent cooling system, reliable performance • under the harshest conditions (ambient temperature up to 40°C and altitudes up to 1000m)
- Self-diagnostic capability simplifies troubleshooting
- LCD display shows system status setup • information

Color choices:



- . sensitive electronics from harmonic distortion and unstable power quality
- Soundproof type: Very quite running: 66±3dB(A) at 23ft(7m) at normal load.
- Enclosed muffler for added guietness •
- Service and; maintenance accessible through easy-latch side service door

Generator Data

| Prime Power (kVA) | 9 |
|--------------------------------------|---------------|
| Standby Power (kVA) | |
| Rated Frequency (Hz) | 50 |
| Running Noise db(A)/7m (Silent type) | 66±3 |
| VItage (V) | 230/380 |
| Curent (A) | 15.3 |
| No.Phase | 3 |
| Silent Type-Dimension (LxWxH) (mm) | 1700*850*1050 |
| Silent Type-Weight (kg) | 850 |
| Fuel Tank Capacity (L) | 20 |
| Fuel | Diesel |
| YDS-10T | Page 1 |





Engine Specifications

Main features:

Brand: YANMAR

- 3-cylinder, water-cooled, in-line diesel engine.
- Efficient fuel system for max power output and durability.
- Large-capacity air cleaner.
- Cost effective, fuel efficient and reliable performance.
- Functional engine with compact structure.
- Excellent after-sales service and sufficient spare parts supplying.
- Easy installation and ready access for routine maintenance

| Model | 3TNV82A-GGE |
|------------------------|-----------------|
| Output Power (kw) | 11 |
| Cylinder No. & Config. | 3, In-line |
| Туре | 4 cycle, Diesel |
| Displacement (liters) | 1.331 |
| Governor | Mechanical type |
| Engine System (r/min) | 1500 |
| Air intake system | Naturally |
| Fuel Consumption (L/h) | 2.3 |
| Oil Capacity (L) | 5.5 |
| Compression ratio | 19.2 |

Alternator specifications

Main Features:

- Advanced automatic voltage regulator (AVR) control for trouble-free operation under the most demanding conditions.
- 2/3 pitch winding as standard, to avoid excessive neutral current.
- Single or two bearing construction with dynamically balanced rotor and sealed-for-life bearings.
- Easy access for installation and maintenance.
- IP23 as standard.
- Self-excited control system.
 Resist of corruption of oil and acid.

| Brand options: | Mecc-Atle/ Leroy Somer/ Benzen |
|-------------------|--------------------------------|
| Model | (M-7) |
| Rated Power (kVA) | 9 |
| Excitation System | Brushless, self-exciting |
| Connection Type | 3 phases, 4 wires |
| Pole No | 4 |
| Regulator type | AVR |
| Protection class | IP23 |
| Insulation class | н |





Options:



Control Panel System



DATAKOM



DEEP SEA

Main Features:

- Using microprocessor as a core, graphics LCD with big screen and backlight, key touch for operation
- All parameters use digital modulation, with higher reliability and stability
- Built-in speed/frequency detecting units can accurately judge the states such as crank success and over speed

Precision measure and display of:

- Generator voltage
- Generator current
- Generator frequency
- Generator active power (kW)
- Generator inactive power (kW)
- Generator apparent power (kVA)
- Generator power factor
- Generator starts count
- Generator hour count
- Cumulate electric energy (kWh)
- Generator temperature
- Generator pressure
 - Start battery voltage

- Security password-protected programming levels
- Power supply range is wide, accommodating to different starting battery voltage environment
- Built-in watch dog can never be dead halt, ensuring smooth program execution
- Modular configuration design, inserted type connection terminals, flush type installation, compact structure, easy installation

Protection:

- Emergency stop
- High water temperature
- Low oil pressure
 - Over speed
- Under speed
- Loss of speed signal
- Generator over frequency
- Generator under frequency
- Generator over voltage
- Generator under voltage
- Generator over current
- Fail to start
 - Auxiliary inputs

* Reserves the right to change the specifications and designs without notice.



СОМАР