

Model: BZ3RD-4A/1S

Model: BZ3RD-6A/3S

BZ3RD-4A/1S / BZ3RD-4A/3S

Frequency	50Hz
Voltage	220V
Max. Power	3.5 kW
Rated Power	3.0 kW
DC Output	12V/8.3 A
Power Factor cos	1 / 0.8
Model	178F
Max. Output	6HP-3600rpm
Displacement	296ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.1L
Dimension (L*W*H)	950*560*730mm
Gross Weight	135kg

BZ3RD-6A/1S / BZ3RD-6A/3S

Frequency	50Hz
Voltage	220V
Max. Power	5.5 kW
Rated Power	5.0 kW
DC Output	12V/8.3 A
Power Factor cos	1 / 0.8
Model	186FA
Max. Output	10HP-3600rpm
Displacement	418ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.1L
Dimension (L*W*H)	950*560*730mm
Gross Weight	150kg

BZ3RD-4A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	3.5kW
Rated Power	3.0kW
DC Output	12V/8.3A
Power Factor cos	0.8
Model	178F
Max. Output	6HP-3600rpm
Displacement	296ml
Noise Level (at 7m)	82dB
Starting System	Recoil
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.1L
Dimension (L*W*H)	740*500*630mm
Gross Weight	86kg

BZ3RD-6A/1L / BZ3RD-6A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	5.5kW
Rated Power	5.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	186FA
Max. Output	10HP-3600rpm
Displacement	418ml
Noise Level (at 7m)	82dB
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	740*500*630mm
Gross Weight	106kg

Model: BZ3RD-60/1S

Model: BZ3RD-7A/3S

BZ3RD-60/1S / BZ3RD-60/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	5.5kW
Rated Power	5.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	186FA
Max. Output	10HP-3600rpm
Displacement	418ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, oil-cooled
Fuel Tank	15L
Oil Capacity	1.65L
Dimension (L*W*H)	950*560*730mm
Gross Weight	154kg

BZ3RD-7A/1S / BZ3RD-7A/3S

Frequency	50Hz
Voltage	220V
Max. Power	6.5kW
Rated Power	6.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	192F
Max. Output	12HP-3600rpm
Displacement	498ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	950*560*730mm
Gross Weight	160kg

BZ3RD-7A/1L / BZ3RD-7A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	6.5kW
Rated Power	6.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	190F
Max. Output	11HP-3600rpm
Displacement	476ml
Noise Level (at 7m)	85dB
Starting System	Recoil
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	740*500*630mm
Gross Weight	111kg

BZ3RD-8A/1L / BZ3RD-8A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	7.5kW
Rated Power	7.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	195F
Max. Output	13HP-3600rpm
Displacement	531ml
Noise Level (at 7m)	85dB
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	770*540*680mm
Gross Weight	116kg

Model: BZ3RD-70/1S

Model: BZ3RD-7A/3S

BZ3RD-70/1S / BZ3RD-70/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	6.5kW
Rated Power	6.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	190F
Max. Output	11HP-3600rpm
Displacement	476ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, oil-cooled
Fuel Tank	15L
Oil Capacity	1.65L
Dimension (L*W*H)	950*560*730mm
Gross Weight	164kg

BZ3RD-7A/1S / BZ3RD-7A/3S

Frequency	50Hz
Voltage	220V
Max. Power	6.5kW
Rated Power	6.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	192F
Max. Output	12HP-3600rpm
Displacement	498ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	950*560*730mm
Gross Weight	160kg

BZ3RD-7A/1L / BZ3RD-7A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	6.5kW
Rated Power	6.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	190F
Max. Output	11HP-3600rpm
Displacement	476ml
Noise Level (at 7m)	85dB
Starting System	Recoil
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	740*500*630mm
Gross Weight	111kg

BZ3RD-8A/1S / BZ3RD-8A/3S

Frequency	50Hz
Voltage	220V
Max. Power	7.5kW
Rated Power	7.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	195F
Max. Output	13HP-3600rpm
Displacement	531ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	950*560*730mm
Gross Weight	164kg

Model: BZ3RD-80/3S

Model: BZ3RD-9A/1S

BZ3RD-80/1S / BZ3RD-80/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	7.5kW
Rated Power	7.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	192F
Max. Output	12HP-3600rpm
Displacement	498ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, oil-cooled
Fuel Tank	15L
Oil Capacity	1.65L
Dimension (L*W*H)	950*560*730mm
Gross Weight	169kg

BZ3RD-9A/1S / BZ3RD-9A/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	10kW
Rated Power	9.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	1100F
Max. Output	15HP-3600rpm
Displacement	667ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	15L
Oil Capacity	2L
Dimension (L*W*H)	1130*640*860mm
Gross Weight	200kg

BZ3RD-9A/1L / BZ3RD-9A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	8.5kW
Rated Power	8.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	1100F
Max. Output	15HP-3600rpm
Displacement	667ml
Noise Level (at 7m)	85dB
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	12.5L
Oil Capacity	1.65L
Dimension (L*W*H)	770*540*680mm
Gross Weight	134kg

BZ3RD-90/1S / BZ3RD-90/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	8.5kW
Rated Power	8.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	195F
Max. Output	13HP-3600rpm
Displacement	531ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, oil-cooled
Fuel Tank	15L
Oil Capacity	1.65L
Dimension (L*W*H)	950*560*730mm
Gross Weight	173kg

Model: BZ3RD-8W/1S

Model: BZ3RD-9W/3S

BZ3RD-8W/1S / BZ3RD-8W/3S

Alternator type	DTF(W)-8.0
Max. Power	8kVA
Rated Power	7kVA
Power Factor cos	1 / 0.8
Model	195F
Rated AC voltage	400/230V
Rated current	28.3
Frequency	50Hz
DC Output	12V/8.3A
Displacement	498ml
Starting System	Electric
Type	Single cylinder, 4-stroke, water-cooled
Fuel tank	15L
Fuel Consumption	8h
Water tank	3.5L
Noise Level (at 7m)	66dB
Oil Capacity	1.65L
Dimension (LxWxH)	1170*610*820mm
Net Weight	191kg

BZ3RD-9W/1S / BZ3RD-9W/3S

Alternator type	DTF(W)-9.0
Max. Power	9kVA
Rated Power	8kVA
Power Factor cos	1 / 0.8
Model	198F
Rated AC voltage	400/230V
Rated current	30.4
Frequency	50Hz
DC Output	12V/8.3A
Displacement	531ml
Starting System	Electric
Type	Single cylinder, 4-stroke, water-cooled
Fuel tank	15L
Fuel Consumption	8h
Water tank	3.5L
Noise Level (at 7m)	67dB
Oil Capacity	1.65L
Dimension (LxWxH)	1240*700*900mm
Net Weight	237kg

Model: BZ3RD-10A/1S

Model: BZ3RD-11A/3S

BZ3RD-10A/1S / BZ3RD-10A/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	10kW
Rated Power	9.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	1105F
Max. Output	18HP-3600rpm
Displacement	736ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	15L
Oil Capacity	2L
Dimension (L*W*H)	1130*640*860mm
Gross Weight	205kg

BZ3RD-11A/1S / BZ3RD-11A/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	11kW
Rated Power	10kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	1105F
Max. Output	20HP-3600rpm
Displacement	736ml
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	15L
Oil Capacity	2L
Dimension (L*W*H)	1130*640*860mm
Gross Weight	220kg

BZ3RD-10A/1L / BZ3RD-10A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	10kW
Rated Power	9.0kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	1105F
Max. Output	20HP-3600rpm
Displacement	736ml
Noise Level (at 7m)	85dB
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	15L
Oil Capacity	2L
Dimension (L*W*H)	770*540*700mm
Gross Weight	175kg

BZ3RD-11A/1L / BZ3RD-11A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	11kW
Rated Power	10kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	1105F
Max. Output	20HP-3600rpm
Displacement	736ml
Noise Level (at 7m)	85dB
Starting System	Electric
Type	Single cylinder vertical, 4-stroke, air-cooled
Fuel Tank	15L
Oil Capacity	2L
Dimension (L*W*H)	770*540*700mm
Gross Weight	182kg

Model: BZ3RD-11W/3S

Model: BZ3RD-13W/1S

BZ3RD-11W/1S / BZ3RD-11W/3S

Alternator type	DTF(W)-11.0
Max. Power	11kVA
Rated Power	10kVA
Power Factor cos	1 / 0.8
Model	1102F
Rated AC voltage	400/230V
Rated current	34.8
Frequency	50Hz
DC Output	12V/8.3A
Displacement	718ml
Starting System	Electric
Type	Single cylinder, 4-stroke, water-cooled
Fuel tank	25L
Fuel Consumption	10h
Water tank	3.5L
Noise Level (at 7m)	69~71dB
Oil Capacity	1.65L
Dimension (LxWxH)	1240*700*900mm
Net Weight	240kg

BZ3RD-13W/1S / BZ3RD-13W/3S

Alternator type	DTF(W)-12.0
Max. Power	12kVA
Rated Power	11kVA
Power Factor cos	1 / 0.8
Model	1105F
Rated AC voltage	400/230V
Rated current	39.1
Frequency	50Hz
DC Output	12V/8.3A
Displacement	762ml
Starting System	Electric
Type	Single cylinder, 4-stroke, water-cooled
Fuel tank	25L
Fuel Consumption	9h
Water tank	3.5L
Noise Level (at 7m)	69~71dB
Oil Capacity	1.65L
Dimension (LxWxH)	1240*700*900mm
Net Weight	246kg

BZ3RD-14A/1S / BZ3RD-14A/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	14kW
Rated Power	12kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	2V92
Max. Output	22HP-3600rpm
Displacement	997ml
Starting System	Electric
Type	Two-cylinder, V-twin, air-cooled, direct injection
Fuel Tank	30L
Oil Capacity	3.8L
Dimension (L*W*H)	1250*650*880mm
Gross Weight	260kg

BZ3RD-18A/1S / BZ3RD-18A/3S

Frequency	50Hz
Voltage	220V/380V
Max. Power	17kW
Rated Power	15kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	2V95
Max. Output	29HP-3600rpm
Displacement	1247ml
Starting System	Electric
Type	Two-cylinder, V-twin, air-cooled, direct injection
Fuel Tank	30L
Oil Capacity	4L
Dimension (L*W*H)	1250*650*880mm
Gross Weight	285kg

Model: BZ3RD-13W/3L

Model: BZ3RD-14W/1L

BZ3RD-13W/1L / BZ3RD-13W/3L

Alternator type	DTF(W)-12.0
Max. Power	12kVA
Rated Power	11kVA
Power Factor cos	1 / 0.8
Model	1102F
Rated AC voltage	400/230V
Rated current	34.8
Frequency	50Hz
DC Output	12V/8.3A
Displacement	718ml
Starting System	Electric
Type	Single cylinder, 4-stroke, water-cooled
Fuel tank	25L
Fuel Consumption	9h
Water tank	30L
Noise Level (at 7m)	85dB
Oil Capacity	1.65L
Dimension (LxWxH)	830*610*780mm
Net Weight	147kg

BZ3RD-14W/1L / BZ3RD-14W/3L

Alternator type	DTF(W)-13.0
Max. Power	13kVA
Rated Power	12kVA
Power Factor cos	1 / 0.8
Model	1105F
Rated AC voltage	400/230V
Rated current	39.1
Frequency	50Hz
DC Output	12V/8.3A
Displacement	762ml
Starting System	Electric
Type	Single cylinder, 4-stroke, water-cooled
Fuel tank	25L
Fuel Consumption	9h
Water tank	30L
Noise Level (at 7m)	85dB
Oil Capacity	1.65L
Dimension (LxWxH)	830*610*780mm
Net Weight	150kg

BZ3RD-18A/1L / BZ3RD-18A/3L

Frequency	50Hz
Voltage	220V/380V
Max. Power	17kW
Rated Power	15kW
DC Output	12V/8.3A
Power Factor cos	1 / 0.8
Model	2V95
Max. Output	29HP-3600rpm
Displacement	1247ml
Noise Level (at 7m)	86dB
Starting System	Electric
Type	Two-cylinder, V-twin, air-cooled, direct injection
Fuel Tank	30L
Oil Capacity	4L
Dimension (L*W*H)	1140*840*1080mm
Gross Weight	285kg