

**Powered by****Genset**

Prime Power (kVA)	725
Standby Power (kVA)	800
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	~1098
Battery Capacity (V-Ah)	24
Fuel Consumption (L/h)	138.4
Running Noise (db(A)@7m)*	90±3@7m
Silent Type-Dimension (mm)	
Fuel (L)	Option
Silent Type-Weight (kg)	
Power factor	0.8

Control Panel System**DSE6120**

USB and DSENet® connectivity for system expansion.
CAN engine support, frequency sensors, and common sensors (0 V - 10 V, 4 mA - 20 mA).



Supports ATS (Automatic Transfer Switch) connection for automatic source switching between mains and generator.

Engine

Model	KT38-GA
-------	---------

Origin	China
--------	-------

Brand	Cummins
-------	---------

Cylinder No. & Config	V12
-----------------------	-----

Compression ratio	14.5:1
-------------------	--------

Output Power (kW)	711
-------------------	-----

Governor	Electrical
----------	------------

Coolant Capacity (L)	66
----------------------	----

Oil Capacity (L)	135.1
------------------	-------

Displacement (L)	38L
------------------	-----

Bore x Stroke	159x159mm
---------------	-----------

Air intake system	Turbocharged
-------------------	--------------

Alternator

Brand Alternator	Benzen Power
------------------	--------------

Model Alternator	BZ0634C
------------------	---------

Rated Power (kVA)	760
-------------------	-----

Insulation class	H
------------------	---

Protection class	IP23
------------------	------

Connection Type	3 phase, 4 pole
-----------------	-----------------

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.