

**Powered by****Genset**

Prime Power (kVA)	910
Standby Power (kVA)	1000
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	~1379
Battery Capacity (V-Ah)	24
Fuel Consumption (L/h)	149.77
Running Noise (db(A)@7m)*	90±3@7m
Silent Type-Dimension (mm)	
Fuel (L)	Option
Silent Type-Weight (kg)	
Power factor	0.8

Control Panel System**DSE6120**

USB and DSENet® connectivity for system expansion.
CAN engine support, frequency sensors, and common sensors (0 V - 10 V, 4 mA - 20 mA).



Supports ATS (Automatic Transfer Switch) connection for automatic source switching between mains and generator.

Engine

Model KTA38-G2A

Origin China

Brand Cummins

Cylinder No. & Config V12

Compression ratio 14.5:1

Output Power (kW) 896

Governor Electrical

Coolant Capacity (L) 66

Oil Capacity (L) 135.1

Displacement (L) 38L

Bore x Stroke 159x159mm

Air intake system Turbocharged .
Aftercooled

Alternator

Brand Alternator Benzen Power

Model Alternator BZN634E

Rated Power (kVA) 950

Insulation class H

Protection class IP23

Connection Type 3 phase, 4 pole

1500 rpm generator specifications

** Reserves the right to change the specifications and designs without notice.*