



*Illustrative image

Powered by



Genset

Prime Power (kVA)	120
Standby Power (kVA)	132
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	182
Battery Capacity (V-Ah)	24V
Fuel Consumption (L/h)*	20
Running Noise (db(A)@7m)*	73±3
Silent Type-Dimension (mm)*	2800x1080x1400
Fuel (L)*	157
Silent Type-Weight (kg)*	1550
Power factor	0,8

Control Panel System

Option:

Deepsea/DatKOM/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

Model	6BTA5.9-G2
Origin	Trung Quốc
Brand	Cummins
Cylinder No. & Config	6L
Compression ratio	17.3:1
Output Power (kW)	116
Governor	Electrical
Coolant Capacity (L)	10
Oil Capacity (L)	16,4
Displacement (L)	5,9L
Bore x Stroke	102x120mm
Air intake system	Turbocharged & Aftercooled

Alternator

Brand Alternator	Stamford/Leroy-Somer/Mecc Alte/Benzen Power
Rated Power (kVA)	120
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.