



*Illustrative image

Powered by



Genset

Prime Power (kVA)	180
Standby Power (kVA)	200
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	285
Battery Capacity (V-Ah)	24V
Fuel Consumption (L/h)*	31
Running Noise (db(A)@7m)*	73±3
Silent Type-Dimension (mm)*	3200x1130x1700
Fuel (L)*	317
Silent Type-Weight (kg)*	2040
Power factor	0,8

Control Panel System

Option:

Deepsea/DatKOM/ComAp/Smartgen/MeBay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

Model	6CTA8.3-G1
Origin	Trung Quốc
Brand	Cummins
Cylinder No. & Config	6L
Compression ratio	17.3:1
Output Power (kW)	180
Governor	Mechanical
Coolant Capacity (L)	12,3
Oil Capacity (L)	27,6
Displacement (L)	8,3L
Bore x Stroke	114x135mm
Air intake system	Turbocharged & Aftercooled

Alternator

Brand Alternator	Stamford/Leroy-Somer/Mecc Alte/Benzen Power
Rated Power (kVA)	180
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.