



\*Illustrative image

Powered by



### Genset

Prime Power (kVA)	200
Standby Power (kVA)	220
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	~300
Battery Capacity (V-Ah)	24V
Fuel Consumption (L/h)*	34
Running Noise (db(A)@7m)*	75±3
Silent Type-Dimension (mm)*	3300x1200x1850
Fuel (L)*	410
Silent Type-Weight (kg)*	2000
Power factor	0,8

### Control Panel System

#### Option:

Deepsea/DatKOM/ComAp/  
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.  
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



### Engine

Model	6CTAA8.3-G2
Origin	Trung Quốc
Brand	Cummins
Cylinder No. & Config	6L
Compression ratio	18.0:1
Output Power (kW)	203
Governor	Electrical
Coolant Capacity (L)	12,3
Oil Capacity (L)	23,8
Displacement (L)	8,3L
Bore x Stroke	114x135mm
Air intake system	Turbocharged and Charge Air Cooled

### Alternator

Brand Alternator	Stamford/Leroy-Somer/Mecc Alte/Benzen Power
Rated Power (kVA)	200
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

## 1500 rpm generator specifications

\* Reserves the right to change the specifications and designs without notice.