



*Illustrative image

Powered by



Genset

Prime Power (kVA)	240
Standby Power (kVA)	264
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	
Battery Capacity (V-Ah)	24V
Fuel Consumption (L/h)*	39
Running Noise (db(A)@7m)*	75±3
Silent Type-Dimension (mm)*	3500x1350x1950
Fuel (L)*	460
Silent Type-Weight (kg)*	2550
Power factor	0,8

Control Panel System

Option:

Deepsea/DatKOM/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

Model	6LTA8.9-G2
Origin	Trung Quốc
Brand	Cummins
Cylinder No. & Config	6L
Compression ratio	16.6:1
Output Power (kW)	240
Governor	Electrical
Coolant Capacity (L)	11,1
Oil Capacity (L)	27,6
Displacement (L)	8,9L
Bore x Stroke	114x145mm
Air intake system	Turbocharged and Charge Air Cooled

Alternator

Brand Alternator	Stamford/Leroy-Somer/Mecc Alte/Benzen Power
Rated Power (kVA)	240
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.