



*Illustrative image

Powered by



Genset

Prime Power (kVA)	350
Standby Power (kVA)	385
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	530
Battery Capacity (V-Ah)	24V
Fuel Consumption (L/h)*	56.5
Running Noise (db(A)@7m)*	75±3
Silent Type-Dimension (mm)*	4500x1700x2390
Fuel (L)*	600
Silent Type-Weight (kg)*	4500
Power factor	0,8

Control Panel System

Option:

Deepsea/Datakom/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

Model	6ZTAA13-G3
Origin	Trung Quốc
Brand	Cummins
Cylinder No. & Config	6L
Compression ratio	17:1
Output Power (kW)	380
Governor	Điện tử
Coolant Capacity (L)	23,1
Oil Capacity (L)	45,42
Displacement (L)	13
Bore x Stroke	130x163mm
Air intake system	Turbocharged & Charge Air Cooled

Alternator

Brand Alternator	Stamford/Leroy-Somer/Mecc Alte/Benzen Power
Rated Power (kVA)	350
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.