



*Illustrative image

Powered by



Genset

| | |
|-----------------------------|-----------------|
| Prime Power (kVA) | 80 |
| Standby Power (kVA) | 86 |
| No.Phase | 3 |
| Voltage/Frequency | 220/380V - 50Hz |
| Engine speed (rpm) | 1500 |
| Current (A) | 121 |
| Battery Capacity (V-Ah) | 24V |
| Fuel Consumption (L/h)* | 13,2 |
| Running Noise (db(A)@7m)* | 72±3 |
| Silent Type-Dimension (mm)* | 2600x1000x1300 |
| Fuel (L)* | 157 |
| Silent Type-Weight (kg)* | 1490 |
| Power factor | 0,8 |

Control Panel System

Option:

Deepsea/DatKOM/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

| | |
|-----------------------|----------------------------|
| Model | 4BTA3.9-G11 |
| Origin | Trung Quốc |
| Brand | Cummins |
| Cylinder No. & Config | 4L |
| Compression ratio | 17.3:1 |
| Output Power (kW) | 80 |
| Governor | Điện tử |
| Coolant Capacity (L) | 8,3 |
| Oil Capacity (L) | 10,9 |
| Displacement (L) | 3,9L |
| Bore x Stroke | 102x120mm |
| Air intake system | Turbocharger & Aftercooler |

Alternator

| | |
|-------------------|---|
| Brand Alternator | Stamford/Leroy-Somer/Mecc Alte/Benzen Power |
| Rated Power (kVA) | 80 |
| Insulation class | H |
| Protection class | IP23 |
| Connection Type | 3 phase, 4 pole |

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.