



\*Illustrative image

Powered by



### Genset

Prime Power (kVA)	188
Standby Power (kVA)	206
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	285
Battery Capacity (V-Ah)	24
Fuel Consumption (L/h)*	29,5
Running Noise (db(A)@7m)*	73±3
Silent Type-Dimension (mm)*	3100x1100x1500
Fuel (L)*	290
Silent Type-Weight (kg)*	1700
Power factor	0,8

### Control Panel System

#### Option:

Deepsea/Datakom/ComAp/  
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.  
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



### Engine

Model	YCA7.3TAA245-G20
Origin	China
Brand	Yuchai
Cylinder No. & Config	6L
Compression ratio	17.5:1
Output Power (kW)	165
Governor	Mechanical
Coolant Capacity (L)	54,66
Oil Capacity (L)	24
Displacement (L)	7,255
Bore x Stroke	108x132
Air intake system	Turbocharged, air-air intercooled

### Alternator

Brand Alternator	Stamford/ Mecc Alte/ Leroysoner/ Benzen Power
Rated Power (kVA)	188
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

## 1500 rpm generator specifications

\* Reserves the right to change the specifications and designs without notice.