



*Illustrative image

Powered by



Genset

| | |
|-----------------------------|-----------------|
| Prime Power (kVA) | 25 |
| Standby Power (kVA) | 27,5 |
| No.Phase | 3 |
| Voltage/Frequency | 220/380V - 50Hz |
| Engine speed (rpm) | 1500 |
| Current (A) | 38 |
| Battery Capacity (V-Ah) | 24 |
| Fuel Consumption (L/h)* | 5,2 |
| Running Noise (db(A)@7m)* | 70±3 |
| Silent Type-Dimension (mm)* | 2000x900x1150 |
| Fuel (L)* | 58 |
| Silent Type-Weight (kg)* | 810 |
| Power factor | 0,8 |

Control Panel System

Option:

Deepsea/Datakom/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

| | |
|-----------------------|---------------|
| Model | YCV2.5N35-G20 |
| Origin | China |
| Brand | Yuchai |
| Cylinder No. & Config | 4L |
| Compression ratio | 17.5:1 |
| Output Power (kW) | 23 |
| Governor | Mechanical |
| Coolant Capacity (L) | 13,5 |
| Oil Capacity (L) | 6,5 |
| Displacement (L) | 2,5 |
| Bore x Stroke | 89x100 |
| Air intake system | Naturally |

Alternator

| | |
|-------------------|--|
| Brand Alternator | Stamford/ Mecc Alte/ Leroysoner/ Benzen Power |
| Rated Power (kVA) | 25 |
| Insulation class | H |
| Protection class | IP23 |
| Connection Type | 3 phase, 4 pole |

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.