



*Illustrative image

Powered by



Genset

Prime Power (kVA)	400
Standby Power (kVA)	440
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	606
Battery Capacity (V-Ah)	24
Fuel Consumption (L/h)*	67,4L
Running Noise (db(A)@7m)*	75±3
Silent Type-Dimension (mm)*	4200x1260x2200
Fuel (L)*	510
Silent Type-Weight (kg)*	3700
Power factor	0,8

Control Panel System

Option:

Deepsea/Datakom/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

Model	YCMJ12540-G30
Origin	China
Brand	Yuchai
Cylinder No. & Config	6L
Compression ratio	14:1
Output Power (kW)	365
Governor	Electronic
Coolant Capacity (L)	84,5
Oil Capacity (L)	37
Displacement (L)	11,73
Bore x Stroke	131x145
Air intake system	Turbocharged, air-air intercooled

Alternator

Brand Alternator	Stamford/ Mecc Alte/ Leroysoner/ Benzen Power
Rated Power (kVA)	400
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.