



\*Illustrative image

Powered by



### Genset

Prime Power (kVA)	40
Standby Power (kVA)	44
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	61
Battery Capacity (V-Ah)	24
Fuel Consumption (L/h)*	8,4
Running Noise (db(A)@7m)*	70±3
Silent Type-Dimension (mm)*	2150x900x1150
Fuel (L)*	58
Silent Type-Weight (kg)*	890
Power factor	0,8

### Control Panel System

#### Option:

Deepsea/Datakom/ComAp/  
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.  
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



### Engine

Model	YCV2.5T55-G20
Origin	China
Brand	Yuchai
Cylinder No. & Config	4L
Compression ratio	17.5:1
Output Power (kW)	38
Governor	Mechanical
Coolant Capacity (L)	13,5
Oil Capacity (L)	6,5
Displacement (L)	2,5
Bore x Stroke	89x100
Air intake system	Turbo supercharging

### Alternator

Brand Alternator	Stamford/ Mecc Alte/ Leroysoner/ Benzen Power
Rated Power (kVA)	40
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

## 1500 rpm generator specifications

\* Reserves the right to change the specifications and designs without notice.