



*Illustrative image

Powered by



Genset

Prime Power (kVA)	62,5
Standby Power (kVA)	68,8
No.Phase	3
Voltage/Frequency	220/380V - 50Hz
Engine speed (rpm)	1500
Current (A)	91
Battery Capacity (V-Ah)	24
Fuel Consumption (L/h)*	12,4
Running Noise (db(A)@7m)*	72±3
Silent Type-Dimension (mm)*	2300x960x1250
Fuel (L)*	111
Silent Type-Weight (kg)*	1000
Power factor	0,8

Control Panel System

Option:

Deepsea/Datakom/ComAp/
Smartgen/ Mebay

User-friendly LCD display for intuitive operation.
Comprehensive monitoring of all generator parameters.

Integrated emergency stop and multi-fault alarms (speed, load, fuel, temperature).



Engine

Model	YCD4.2T90-G20
Origin	China
Brand	Yuchai
Cylinder No. & Config	4L
Compression ratio	17.5:1
Output Power (kW)	60
Governor	Mechanical
Coolant Capacity (L)	30
Oil Capacity (L)	13
Displacement (L)	4,2
Bore x Stroke	108x115
Air intake system	Turbocharged

Alternator

Brand Alternator	Stamford/ Mecc Alte/ Leroysoner/ Benzen Power
Rated Power (kVA)	62,5
Insulation class	H
Protection class	IP23
Connection Type	3 phase, 4 pole

1500 rpm generator specifications

* Reserves the right to change the specifications and designs without notice.